

Material	Dielectric constant ($\kappa = \epsilon/\epsilon_0$) () is $(\kappa-1) \times 10^6$ for gas	Young's modulus [10 ⁶ psi]	Coeff. of thermal expansion [10 ⁻⁶ cm/cm·°C]	Specific heat [cal/g·°C]	Electrical resistivity [μΩcm(@°C)]	Thermal conductivity [cal/cm·°C·sec]
H ₂	(253.9)	—	—	—	—	—
He	(64)	—	—	—	—	—
Li	—	—	56	0.86	8.55(0°)	0.17
Be	—	37	12.4	0.436	5.885(0°)	0.38
C	—	0.7	0.6–4.3	0.165	1375(0°)	0.057
N ₂	(548.5)	—	—	—	—	—
O ₂	(495)	—	—	—	—	—
Ne	(127)	—	—	—	—	—
Al	—	10	23.9	0.215	2.65(20°)	0.53
Si	11.9	16	2.8–7.3	0.162	—	0.20
Ar	(517)	—	—	—	—	—
Ti	—	16.8	8.5	0.126	50(0°)	—
Fe	—	28.5	11.7	0.11	9.71(20°)	0.18
Cu	—	16	16.5	0.092	1.67(20°)	0.94
Ge	16.0	—	5.75	0.073	—	0.14
Sn	—	6	20	0.052	11.5(20°)	0.16
Xe	—	—	—	—	—	—
W	—	50	4.4	0.032	5.5(20°)	0.48
Pt	—	21	8.9	0.032	9.83(0°)	0.17
Pb	—	2.6	29.3	0.038	20.65(20°)	0.083
U	—	—	36.1	0.028	29(20°)	0.064

1. R.M. Sternheimer, M.J. Berger, and S.M. Seltzer, Atomic Data and Nuclear Data Tables **30**, 261–271 (1984).
 2. S.M. Seltzer and M.J. Berger, Int. J. Appl. Radiat. **33**, 1189–1218 (1982).
 3. D.E. Groom, N.V. Mokhov, and S.I. Striganov, “Muon stopping-power and range tables,” Atomic Data and Nuclear Data Tables **78**, 183–356 (2001).
 4. S.M. Seltzer and M.J. Berger, Int. J. Appl. Radiat. **35**, 665 (1984) & <http://physics.nist.gov/PhysRefData/Star/Text/contents.html>.
- a. σ_T , λ_T and λ_I are energy dependent. Values quoted apply to high energy range, where energy dependence is weak. Mean free path between collisions (λ_T) or inelastic interactions (λ_I), calculated from $\lambda^{-1} = N_A \sum w_j \sigma_j / A_j$, where N is Avogadro’s number and w_j is the weight fraction of the j th element in the element, compound, or mixture. σ_{total} at 80–240 GeV for neutrons ($\approx \sigma$ for protons) from Murthy *et al.*, Nucl. Phys. **B92**, 269 (1975). This scales approximately as $A^{0.77}$. $\sigma_{\text{inelastic}} = \sigma_{\text{total}} - \sigma_{\text{elastic}} - \sigma_{\text{quasielastic}}$; for neutrons at 60–375 GeV from Roberts *et al.*, Nucl. Phys. **B159**, 56 (1979). For protons and other particles, see Carroll *et al.*, Phys. Lett. **80B**, 319 (1979); note that $\sigma_I(p) \approx \sigma_I(n)$. σ_I scales approximately as $A^{0.71}$.
 - b. For minimum-ionizing muons (results are very slightly different for other particles). Minimum dE/dx from Ref. 3, using density effect correction coefficients from Ref. 1. For electrons and positrons see Ref. 4. Ionization energy loss is discussed in Sec. 27.
 - c. From Y.S. Tsai, Rev. Mod. Phys. **46**, 815 (1974); X_0 data for all elements up to uranium are given. Corrections for molecular binding applied for H₂ and D₂. For atomic H, $X_0 = 63.05 \text{ g/cm}^2$.
 - d. For molecular hydrogen (deuterium). For atomic H, $X_0 = 63.047 \text{ g cm}^{-2}$.
 - e. For pure graphite; industrial graphite density may vary 2.1–2.3 g/cm³.
 - f. Standard shielding blocks, typical composition O₂ 52%, Si 32.5%, Ca 6%, Na 1.5%, Fe 2%, Al 4%, plus reinforcing iron bars. The attenuation length, $\ell = 115 \pm 5 \text{ g/cm}^2$, is also valid for earth (typical $\rho = 2.15$), from CERN-LRL-RHEL Shielding exp., UCRL-17841 (1968).
 - g. For typical fused quartz. The specific gravity of crystalline quartz is 2.64.
 - h. Solid ethane density at -60°C ; gaseous refractive index at 0°C , 546 mm pressure.
 - i. Nylon, Type 6, $(\text{NH}(\text{CH}_2)_5\text{CO})_n$
 - j. Polycarbonate (Lexan), $(\text{C}_{16}\text{H}_{14}\text{O}_3)_n$
 - k. Polyethylene terephthalate, monomer, C₅H₄O₂
 - l. Polyethylene, monomer CH₂=CH₂
 - m. Polymide film (Kapton), $(\text{C}_{22}\text{H}_{10}\text{N}_2\text{O}_5)_n$
 - n. Polymethylmethacrylate, monomer CH₂=C(CH₃)CO₂CH₃
 - o. Polystyrene, monomer C₆H₅CH=CH₂
 - p. Teflon, monomer CF₂=CF₂
 - q. Polyvinyltoluene, monomer 2-CH₃C₆H₄CH=CH₂
 - r. Bismuth germanate (BGO), $(\text{Bi}_2\text{O}_3)_2(\text{GeO}_2)_3$
 - s. 97% SiO₂ + 3% H₂O by weight; see A. R. Buzykaev *et al.*, Nucl. Instrum. Methods **A433**, 396 (1999). Aerogel in the density range 0.04–0.06 g/cm³ has been used in Čerenkov counters, but aerogel with higher and lower densities has been produced. ρ = density in g/cm³.
 - t. G10-plate, typically 60% SiO₂ and 40% epoxy.